NEW hook

Mustad Xtra Forged

40 110 XF

For enhanced durability and increased hook capacity

Mustad 40 110 XF – Featuring 2X extra-heavy and extra forged wire, - this hook delivers exceptional strength and durability in both the shank and point. Designed to maximize the hook capacity per magazine and reduce overlapping of hooks, making it ideal for demanding commercial fishing operations.

Feedback from freezer longliner GEIR after trial:

"The crew prefers the new hook with yellow snoods."

The main reasons are reduced rust, less bending or need for replacement, and a more compact fit on the magazines. They also noted that the yellow coating holds up better against wear and tear. In terms of catch performance, our test samples show no difference compared to the previous hook."

Arild Holmeseth, owner and Chief onboard GEIR



Slimmer design and extra-forged construction allow for more hooks per meter on storage magazines, optimizing space without compromising strength.

Reduced Overlap

Improved depth-to-width ratio minimizes overlap, allowing the hooks to slide more easily on the magazines, enhancing both organization and handling.

Enhanced Strength

Built with 2x extra heavy wire, providing outstanding strength and durability in both the shank and point.





Twisted Polyester Gangions

Crafted from durable polyester yarn, these twisted gangions are available with plain ends, sewn loops, or knotted ends. All ready-made snoods are impregnated for added durability.

Industrial Sewing

Our specialized industrial sewing technique ensures uniform loop length across all snoods. This method has been proven stronger than traditional knots and allows the gangions to pass more smoothly through your Mustad Autoline system.

Hooks and Gangions

Hooks and gangions are also available separately to suit your specific needs.

Mustad Autoline AS

PB 41 · N-2801 · Gjøvik · Norway · Phone: +47 70 10 75 80 mail@mustadautoline.com · service@mustadautoline.com www.mustadautoline.com



Key Insights

40 110 XF 40 000 DT Wire dia. 2,67 mm 2,64 mm Forge thickness 2,18 mm 2,30 mm **Depth-with ratio** 1,38 mm 1,20 mm **Strenght** 75 kgf 80 kgf









